

Durham Research Online

Deposited in DRO:

18 June 2019

Version of attached file:

Accepted Version

Peer-review status of attached file:

Peer-reviewed

Citation for published item:

Basu, Tathagata and Einbeck, Jochen and Troffaes, Matthias C. M. and Forbes, Alistair (2019) 'Robust uncertainty quantification for measurement problems with limited information.', ISIPTA 2019 Ghent, Belgium, 3-6 July 2019.

Further information on publisher's website:

<http://www.isipta2019.ugent.be/>

Publisher's copyright statement:

Additional information:

Use policy

The full-text may be used and/or reproduced, and given to third parties in any format or medium, without prior permission or charge, for personal research or study, educational, or not-for-profit purposes provided that:

- a full bibliographic reference is made to the original source
- a [link](#) is made to the metadata record in DRO
- the full-text is not changed in any way

The full-text must not be sold in any format or medium without the formal permission of the copyright holders.

Please consult the [full DRO policy](#) for further details.

Robust Uncertainty Quantification for Measurement Problems with Limited Information.*

Tathagata Basu
Jochen Einbeck
Matthias C. M. Troffaes

Department of Mathematical Sciences, Durham University, UK

TATHAGATA.BASU@DURHAM.AC.UK
JOCHEN.EINBECK@DURHAM.AC.UK
MATTHIAS.TROFFAES@DURHAM.AC.UK

Alistair Forbes

Data Science Group, National Physical Laboratory, UK

ALISTAIR.FORBES@NPL.CO.UK

Metrology has an important role in modern science and relies on the accuracy and repeatability of a measurement. However, these measurements are the outcomes of different expensive experiments and noisy due to the epistemic uncertainty associated with these experiments. We express our model by $y = f(\mu_1, \mu_2, \dots, \mu_m)$, where $\mu := (\mu_1, \dots, \mu_m)$ are m different inputs. Our main goal is to obtain a confidence interval for $f(\mu)$, based on some estimates for μ .

We use the delta method [3] for uncertainty quantification, which is based on the multivariate normal approximation. Let $\hat{X} := (\hat{X}_1, \dots, \hat{X}_m)$ be an estimator of μ such that approximately $\hat{X} \sim N(\mu, \Sigma)$ where $\Sigma := \text{Cov}(\hat{X})$. If f is differentiable, then by first order Taylor expansion, we have

$$f(\hat{X}) \approx f(\mu) + \nabla f(\mu)^T (\hat{X} - \mu). \quad (1)$$

Now, if f is approximately linear around μ for the distributional range of \hat{X} , then we approximately have that $f(\hat{X}) \sim N(f(\mu), \nabla f(\mu)^T \Sigma \nabla f(\mu))$, by Eq. (1) and by the usual linear transformation rule for the covariance matrix. We can use this approximate distribution of $f(\hat{X})$ to construct a 95% confidence interval for $f(\mu)$. However, $f(\hat{X})$ may not be necessarily Gaussian especially if f is highly non-linear. Additionally, for the variance term $\nabla f(\mu)^T \Sigma \nabla f(\mu)$, we may need to use the sample standard deviation as we do not know Σ , and we may need to use $\nabla f(\hat{X})$ as we do not know $\nabla f(\mu)$.

To avoid these issues, we propose using imprecise probability for uncertainty quantification in metrology, which is a new contribution to the field. Specifically, we propose using p-boxes [1]. This helps us to relax distributional assumptions and thereby leads to more robust estimates. Additionally, uncertainty expressed as a p-box can be easily propagated through a range of standard non-linear operators.

We illustrate our results by analysing the uncertainty associated with end gauge calibration [2]. Here, we try to determine the length (ℓ_M) of an end gauge (M) by comparing it with length (ℓ_S) of a known standard (S) using the relation, $\ell_M = \frac{\ell_S(1+\alpha_S\theta_S)+d}{1+\alpha_M\theta_M}$. Here, α_M and θ_M (α_S and θ_S) are thermal expansion coefficient and temperature deviation of M (S) and d is the difference between ℓ_M and ℓ_S . In practice, α_M and θ_M (α_S and θ_S) often have weak correlation between them. Therefore, we use p-boxes to characterise these variables. We inspect their dependence structure for uncertainty propagation and obtain a robust estimate. Finally, we compare our results with the delta method.

References

- [1] Scott Ferson, Vladik Kreinovich, Lev Grinzburg, Davis Myers, and Kari Sentz. Constructing probability boxes and dempster-shafer structures. *Sandia journal manuscript; Not yet accepted for publication*, 5 2015. ISSN 9999-0014. URL <https://www.osti.gov/biblio/1427258>.
- [2] JCGM 100:2008. Evaluation of measurement data – guide to the expression of uncertainty in measurement, 2008. URL <https://www.bipm.org/en/publications/guides>. Accessed: 2019-05-24.
- [3] Aad W. van der Vaart and Jon A. Wellner. *Weak Convergence and Empirical Processes: With Applications to Statistics*. Springer New York, 1996. doi:10.1007/978-1-4757-2545-2.

* This work is funded by the European Commission's H2020 programme, through the UTOPIAE Marie Curie Innovative Training Network, H2020-MSCA-ITN-2016, Grant Agreement number 722734.